



11 kW WiFi connected



EV Swift 1005

LEVEL 2 SMART CHARGER

SPECIFICATIONS

Cloud Service	EV OS
Maximum Output Power	11 kW
Output Power	48 A @200~240 Vac, 1-phase
Vehicle Connector	SAE J1772
Charging Cable Length	16.4 feet / 5 m
Input Power	1-phase, 3-wire, 200~240 Vac, 48 A maximum
Grounding System	TN, TT, IT
Efficiency	> 99%
Power Factor	> 0.99
Display	LED indicator, 5 inch LCD
Communication Protocol	OCPP 1.6 JSON (ready for OCPP 2.0)
Network Connectivity	Ethernet, Wi-Fi
RFID	ISO/IEC 14443 A/B
NEMA enclosures(NEMA)	NEMA 4
Impact Protection	IK10
Electrical protection	Over voltage, under voltage, surge protection, ground fault protection, residual current device, short circuit protection, over current protection, over temperature protection
Operating temperature	-22° to 122° F / -30° to 50° C
Dimensions	11.6 (W) x 19.9 (H) x 5.9 (D) in > 295 (W) x 505 (H) x 150 (D) mm
Weight	19.2 lbs / 8.7 kg
Certifications	UL, FCC, ENERGY STAR

Depth
5.9 in / 150 mm

DIMENSIONS

Height
19.9 in / 505 mm

Width
11.6 in / 295 mm

