



19 kW Cellular connected



EV Swift 1009

LEVEL 2 SMART CHARGER

SPECIFICATIONS

Cloud service	EV OS
Maximum Output Power	19 kW
Output power	80 A @200~240 Vac, 1-phase
Vehicle Connector	SAE J1772
Charging Cable Length	25 feet / 7.6 m
Input Power	220~240 Vac, 80 A maximum; 1-phase, 3-wire
Display	OLED, 20 characters, 2 lines
Grounding System	TN, TT
Communication Protocol	OCPP 1.6 JSON
Network Connectivity	Ethernet, Wi-Fi, 4G (Cat.M1)
RFID	ISO/IEC 14443 A/B
Dust & Water Protection	NEMA 3R
Impact Protection	IK10
Electrical Protection	Over voltage protection, over current protection, under voltage protection, surge protection, short circuit, residual current device, over temperature, ground fault protection
Operating Temperature	-31 °F to +131 °F / -35 °C to +55 °C
Dimensions	10.6 (W) x 14.1 (H) x 5.5 (D) in 270 (W) x 360 (H) x 140 (D) mm
Weight	27.4 lbs / 12.4 kg
Certifications	UL, FCC, Energy Star

DIMENSIONS

Width 10.6 in / 270 mm

Height 14.1 in / 360 mm

Depth 5.5 in / 140 mm

