



7 kW Ethernet connected



EV Swift 1001

LEVEL 2 FAST CHARGER

SPECIFICATIONS

Cloud service	EV OS		
Maximum Output Power	7.6 kW		
Output power	32 A @200~240 Vac, 1-phase		
Vehicle Connector	SAE J1772		
Charging Cable Length	16.4 feet / 5 m		
Input Power	220~240 Vac, 40 A maximum; 1-phase, 3-wire		
Display	LED Indicator		
Grounding System	TN, TT, IT		
Communication Protocol	OCPP 1.6 JSON		
Network Connectivity	Ethernet, Wi-Fi		
RFID	ISO/IEC 14443 A/B		
Dust & Water Protection	NEMA 3R		
Impact Protection	IK08		
Electrical Protection	Over voltage protection, over current protection, under voltage protection, surge protection, short circuit, residual current device, over temperature, ground fault protection		
Operating Temperature	-22 to 122 °F / -30 to 50 °C		
Dimensions	10.2 (W) x 11 (H) x 3.9 (D) in 260 (W) x 280 (H) x 100 (D) mm		
Weight	8.8 lbs / 4 kg	Height	
Certifications	UL, cUL, FCC	11 in / 280 mm	
		Width	Depth
		10.2 in / 260 mm	3.9 in / 100 mm

DIMENSIONS

