



# EVTECH

GENERATING POWER & IDEAS

## 7 kW Dual Port Charger



### EV Swift 1004

Level 2 Fast Charger

# Specifications

ELECTRICAL PROPERTIES	
Power line electrical input	2x 7.2 kW (240 V AC split-phase, 30 A per cable)
Electrical output	Up to 2x 7.2 kW
Charging mode	Level 2 (SAE J1772) / Mode 3 EVSE (IEC 61851)
Fixed charging cable	2x Type 1 (SAE J1772) fixed cables - fully sealed
Charging cable length	18 ft
Metering	Dual UL revenue-grade kWh meter California: CTEP variant available
Service panel breaker	Dual-pole common trip 40 A breaker

ENVIRONMENT AND SAFETY CLASS	
Operating temperature range	-22 °F to +113 °F
Maximum operating humidity (non-regulating)	85% RH (non-condensing)
Maximum installation altitude	6562 ft above sea level
Enclosure degree of protection	IP55 / IK10 / UL 50E (Type 3R)
Ground leakage detection	CCID 20 mA AC per outlet
Surge protection	6 kV

CONNECTIVITY	
Authorization	RFID, QR code, and Autostart
Communication standard	Dual band Wi-Fi 2.4/5 GHz, Bluetooth 4.0 for configuration with the EVBox Connect app, GPS
Communication protocol to backend	OCPP 1.6 J
Charging station configuration	Using EVBox Connect app and OCPP compliant backend

PHYSICAL PROPERTIES	
Dimensions (W x H x D)	16.5" x 72.6" x 11.4" 5"
Weight	188 lbs 210 lbs in packaging
Plastic materials	UL 94 - 5VA / US-FMVSS / ISO 3795 passed, DIN 53438 FI/K1
Locking holster	Quantity 2
Display	8" LCD full color screen (768 x 1024) with capacitive touch, sunlight readable
Status indication	2 LED rings, 1 per connector
Mounting	Ground mount: free-standing, wall-supported, or back-to-back
Cable management	Smart cable management: auto-locking, auto-retractable

CERTIFICATION AND COMPLIANCE	
UL 2594, UL 2231-2, UL 1998-3, UL 991, cULus	
FCC Part 15 Class A	
ISED ICES-003 Class A	
Dual AC Energy Meters: California - CTEP	
Energy Star	
Americans with Disabilities Act (ADA)	



# Dimensions

